
LPNMR in the Age of LLMs

Verification, Policy, and Trustworthy Agency

Chitta Baral

Arizona State University

From an OpenAI employee



https://arxiv.org/pdf/2407.14790

Step-by-Step Reasoning to Solve Grid Puzzles: ... 1 / 18 122%

Step-by-Step Reasoning to Solve Grid Puzzles: Where do LLMs Falter?

Nemika Tyagi[1*] **Mihir Parmar**[1*] **Mohith Kulkarni**[1] **Aswin RRV**[1] **Nisarg Patel**[1]
Mutsumi Nakamura[1] **Arindam Mitra**[2] **Chitta Baral**[1]

[1]Arizona State University [2]Microsoft Research
{ntyagi8, mparmar3, chitta}@asu.edu

EMNLP 2024

2407.14790v2 [cs.CL] 4 Oct 2024

Abstract

Solving grid puzzles involves a significant amount of logical reasoning. Hence, it is a good domain to evaluate the reasoning capability of a model which can then guide us to improve the reasoning ability of models. However, most existing works evaluate only the final predicted answer of a puzzle, without delving into an in-depth analysis of the LLMs' reasoning chains (such as where they falter) or providing any finer metrics to evaluate them. Since LLMs may rely on simple heuristics or artifacts to predict the final answer, it is crucial to evaluate the generated reasoning chain beyond overall correctness measures, for accurately evaluating the reasoning abilities of LLMs. To this end, we first develop *GridPuzzle*, an evaluation dataset comprising 274 grid-based puzzles with different complexities. Second, we propose a new error taxonomy derived from manual analysis of reasoning chains from LLMs including GPT-4, Claude-3, Gemini, Mistral, and Llama-2. Then, we develop an LLM-based framework for large-scale subjective evaluation (i.e., identifying errors) and an objective metric, *PuzzleEval*, to evaluate the correctness of

2023) have achieved remarkable performance on a wide range of Natural Language Understanding (NLU) tasks previously thought to be exclusive to humans. Beyond NLU, exploring LLMs' logical reasoning abilities (Liu et al., 2021; Saparov and He, 2022; Parmar et al., 2024; Patel et al., 2024) on complex tasks such as puzzle-solving is under-explored. Past attempts have been made to evaluate models on logic-intensive grid-based puzzle-solving. However, they either do not focus on evaluating LLMs (Mitra and Baral, 2015; Jabrayilzade and Tekir, 2020) or do not evaluate LLMs independently, but rather use neuro-symbolic approaches (Ishay et al., 2023) that use external specialized solvers on LLM outputs. Here, we aim to evaluate the puzzle-solving abilities of LLMs by themselves, without the use of any external logic solvers.

To understand the reasoning capabilities of LLMs, it is important to evaluate reasoning chains, rather than the final predicted answer. There have been works that evaluate reasoning chains using objective metrics such as ROSCOE (Golovneva et al., 2022), CTC (Deng et al., 2021), and BARTScore (Yuan et al., 2021), however, they do not focus

ZebraLogic: On the Scaling Limits of LLMs for Logical Reasoning. ICML 2025. Yejin Choi and Team.

Arindam Mitra and Chitta Baral. Learning to automatically solve logic grid puzzles. EMNLP 2015.

Chitta Baral and Juraj Dizfcak. Solving puzzles described in English by automated translation to answer set programming and learning how to do that translation. AAAI Fall Symposium on Advances in Cognitive Systems. 2011. A revised but shorter version at KR 2012.

https://aifails.substack.com/p/gpt-6-astra-and-the-human-body


Funny AI fails with Vincent Conitzer



VINCENT CONITZER
SEP 07, 2026

2 Share

While the label “AGI” is thrown around without definition, here’s something GPT-6 Astra can’t do. Though, in this particular case, it’s probably funnier to watch human beings as they answer the question, even though they’ll get it right!




Hard for humans to think without doing!

Vincent Conitzer, September 2, 2026


Not able to prioritize on what is more important. (Damaged drivers license vs seeing a Martian's photo)

Needs to apply commonsense for



Vincent Conitzer, September 1, 2026


Not able to prioritize on what is more important. (ability to bounce or air resistance)



Vincent Conitzer, August 30, 2026

Not applying common-sense.


Loses the nuanced meaning of “fit” while reasoning.



Vincent Conitzer, August 26, 2026

Not understanding.


Phantom recall of similar but different questions.



Vincent Conitzer, August 22, 2026

Not applying common-sense.


Not prioritizing in responding.



Vincent Conitzer, August 11, 2026

Not applying common-sense.

Loses focus.



Some issues from the previous examples – quite relevant to LPNMR

- Common-sense
- Dealing with priorities
- Losing focus while trying to understand (lacks declarativeness)
- Phantom recall – not thinking properly
- More LPNMR relevance - a bit later

https://arxiv.org/pdf/2510.11812
PHANTOM RECALL: When Familiar Puzzles Fool Smart Mod… 1 / 22 135%

PHANTOM RECALL: When Familiar Puzzles Fool Smart Models

Souradeep Mukhopadhyay[1*] **Rishabh Baral**[1*] **Nimeesh Mahajan**[1*] **Samhitha Harish**[1*]
Aswin RRV[1] **Mihir Parmar**[1] **Mutsumi Nakamura**[1] **Chitta Baral**[1]

[1]School of Computing and Augmented Intelligence, Arizona State University
{smukho11, rbaral1, mutsumi, chitta}@asu.edu

arXiv:2510.11812v1 [cs.CL] 13 Oct 2025

Abstract

Large language models (LLMs) such as GPT, Gemini, and Claude often appear adept at solving classic logic puzzles—*but how much genuine reasoning underlies their answers?* Recent evidence suggests that these models frequently rely on memorized templates rather than reasoning from first principles. When puzzles are slightly modified, their performance collapses, revealing a striking fragility. In particular, we asked: *Have LLMs addressed these issues? To what extent? How about perturbations to other puzzles?Is there a general way of reformulating the prompt so that the models do better?* To examine these things systematically, we introduce **PHANTOM RECALL**, a benchmark comprising 25 well-known logic puzzles and 149 carefully designed perturbations that preserve reasoning structure but alter superficial details and solutions. We evaluate eleven leading LLMs and identify a recurring failure mode–phantom recall–where mod-





Figure 1: LLMs stumbled on this simple trivial puzzle variant–but a human can solve it instantly.

with confidence–and was completely wrong. This amusing failure points to something deeper: despite their fluent prose and encyclopedic recall, LLMs often falter on tasks that require precise reasoning and faithful interpretation of instructions. Marcus (2024) catalogs numerous such failures, including

A recent OpenAI blog post on “alignment”



Scalable defense

Pacing RSI

What is next?


Goal alignment is broadly: "does the AI try to accomplish the goal set before it?". This can include things like adherence to an instruction hierarchy, or the ability to communicate and collaborate with people, to attempt to understand their objectives. This set of directions has been extremely practically relevant.

Value alignment is a more intrinsic property of the model. It is the ability to hold and generalize from a high-level set of principles; to act "reasonably" even when given unclear or conflicting objectives, or placed in unfamiliar or adversarial situations. An aligned AI should act with honesty and integrity, and love for humanity.

Of course, the boundary between value and goal alignment can be blurry, and truly caring about goals requires attempting to infer the intent and values underlying them. However, generally when I talk about the long-term importance of alignment research, I am referring to value alignment.

The fundamental challenge of AI alignment is generalization. As machines become smarter, they find themselves working on higher-level concepts, and placed in environments increasingly different from those they encountered in training. They can fail at generalizing from the values taught and reinforced in their training process to those new situations; and it can be hard for us to be sure how they will act. This is made even more difficult by the fact the overall ecosystem the AIs are used in is changing very quickly; for example, AIs trained today need to be robust to interacting with a variety of other AIs. Crucially, we need future AIs to continue to hold human values regardless of whether they believe they're under human supervision.

Let us dive into LLMs



From https://sci-draw.com/llm-architecture-diagram-generator

ML and LLMs - From an EMNLP 2023 workshop talk

2012-2018

Task-specific deep learning

Features

- Develop models for one or a few NLP tasks
- Model quality highly depends on available training data
- Hard to transfer between different tasks

Models

- Recurrent Neural Network
- Convolutional Neural Network
- Transformer
- Complex combination of above

Required Skills

- Expertise in designing and developing complex neural model architecture

2018-2022

Pretrain-Finetune Paradigm

Features

- Large-scale model pre-trained on big data with self-supervised learning
- One base model for all
- Adapt to downstream tasks via fine-tuning

Models

- BERT
- RoBERTa
- BART
- T5

Required Skills

- Ability to fine-tune
- Develop in distributed computing environment

2022-Now

Prompt-based Generalist

Features

- Super-large-scale model pre-trained on very big data with language modeling
- Strong generalist capable of many different tasks
- Adapt via instruction and in-context examples in prompts


Models

- InstructGPT
- ChatGPT
- GPT-4
- LLaMA
- Alpaca

Required Skills


- Write and iterate prompts
- Instruction tuning (only for open LLM such as LLaMA)

Basic LLM Training part in more details



https://huyenchip.com/2023/05/02/rlhf.html


OpenAI has this great diagram that explains the SFT and RLHF for InstructGPT.



SFT and Instruction Tuning

- Earlier categorization of machine learning techniques
  - Unsupervised learning
  - Supervised learning
  - Reinforcement learning
- A recent addition: Instruction Tuning
  - A variation of “Supervised Learning”, where tasks are part of the input.
  - Thus, trained models can do new tasks.

https://yaofu.notion.site/June-2023-A-Stage-Review-of-Instruction-Tuning-f59dbfc36e2d4e12a33443bd6b2012c2



June 2023, A Stage Review of Instruction Tuning

Yao Fu, University of Edinburgh

yao.fu@ed.ac.uk

June 29th 2023

Is this page useful?

Page analytics by Notionlytics

Following the great success of ChatGPT, on February 24, 2023, the emergence of LLaMA heated up the direction of instruction tuning. On March 18, Alpaca demonstrated the potential of distilling smaller models from mature ones to become decent ChatBots, triggering a Cambrian explosion of llama-based models. However, just three months later, people began to recognize the various problems of training LLaMA with ChatGPT's data. This article reviews the development of LLaMA-based models over the past three months and discusses the next challenges of Instruction Tuning.

Disclaimer: This article is essentially a quick research memo, edited from the outline of my recent presentation, with some cuts and additions. Currently, there are many things the open-source community is unclear about building LLMs. I have tried my best to ensure that the content I refer to or discuss has solid evidence, rather than being based on rumors. Much of the content comes from direct discussions with the original authors of the corresponding papers. Even so, my take may still be very wrong and there may be many unresolved issues, so please feel free to comment directly beside the article and participate actively in the discussion — I will keep all the comments that point out my errors. The truth becomes clearer with debate.

1 - The origin

The first three papers:

- **Natural Instructions v1**: Cross-task generalization via natural language crowdsourcing instructions
  - The very beginning. Initially released in **April 2021**. Two years ahead of LLaMA. Extremely visionary!!!
- **FLANv1**: Finetuned Language Models Are Zero-Shot Learners
- **T0**: Multitask Prompted Training Enables Zero-Shot Task Generalization
- **InstructGPT**: Training language models to follow instructions with human feedback

Comparisons:

- The goal of InstructGPT is *alignment*, with zero-shot and cross-lingual being *side effects*.
  - This paper used a 7B Reward model corresponding to a 175B Policy model, which was then followed by DeepSpeed Chat and a series of subsequent RL open-source works. This approach should be incorrect.
  - The correct approach should be to scale up the Reward model to reduce the size of the Policy model, as seen in Scaling Laws for Reward Model Overoptimization — that is, reversing the sizes of the two models, using a 175B Reward to PPO a 7B policy.
  - For the model to be deployed online, 10 - 50B is a more affordable scale, anything larger would be too costly.
- The goals of FLANv1 and T0 are *zero-shot*, so they are *not for alignment*.

Then there's Self-instruct:

- Self-Instruct: Aligning Language Models with Self-Generated Instructions

Important points about self-instruct:

Knowledge Guided Named Entity Recognition for BioMedical Text

Pratyay Banerjee * **Kuntal Kumar Pal*** **Murthy Devarakonda** **Chitta Baral**
Department of Computer Science, Arizona State University
pbanerj6,kkpal,mdevarak,chitta@asu.edu

.03869v4 [cs.CL] 18 Sep 2020

Abstract

In this work, we formulate the NER task as a multi-answer knowledge guided QA task (KGQA) which helps to predict entities only by assigning B, I and O tags without associating entity types with the tags. We provide different knowledge contexts, such as, entity types, questions, definitions and examples along with the text and train on a combined dataset of 18 biomedical corpora. This formulation (a) enables systems to jointly learn NER specific features from varied NER datasets, (b) can use knowledge-text attention to identify words having higher similarity to provided knowledge, improving performance, (c) reduces system confusion by reducing the prediction classes to B, I, O only, and (d) makes detection of nested entities easier. We perform extensive experiments of this KGQA formulation on 18 biomedical NER datasets, and through experiments we note that knowledge helps in achieving better performance. Our problem formulation is able to achieve state-of-the-art results in 12 datasets.




Figure 1: The top block shows the traditional way of NER. In our method, we predict only B, I and O tags for a given context, i.e, only red tags are predicted if the context is about entity Problem.

ral language tasks like commonsense question an-

https://github.com/SinclairCoder/Instruction-Tuning-Papers

README.md

Instruction-Tuning-Papers

PRs welcome | Stars 666

A trend starts from `Natrural-Instruction` (ACL 2022), `FLAN` (ICLR 2022) and `T0` (ICLR 2022).

What's the instruction-tuning? It aims to teach language models to follow natural language (including prompt, positive or negative examples, and constraints etc.), to perform better multi-task learning on training tasks and generalization on unseen tasks.

Papers

1. **Cross-task generalization via natural language crowdsourcing instructions**

   Swaroop Mishra, Daniel Khashabi, Chitta Baral, Hannaneh Hajishirzi [paper] 2021.4

2. **Finetuned language models are zero-shot learners**

   Jason Wei, Maarten Bosma, Vincent Y. Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M. Dai, Quoc V. Le [paper] 2021.9

3. **Multitask Prompted Training Enables Zero-Shot Task Generalization**

   Victor Sanh, Albert Webson, Colin Raffel, Stephen H. Bach, Lintang Sutawika, Zaid Alyafeai, Antoine Chaffin, Arnaud Stiegler, Teven Le Scao, Arun Raja, Manan Dey, M Saiful Bari, Canwen Xu, Urmish Thakker, Shanya Sharma Sharma, Eliza Szczechla, Taewoon Kim, Gunjan Chhablani, Nihal Nayak, Debajyoti Datta, Jonathan Chang, Mike Tian-Jian Jiang, Han Wang, Matteo Manica, Sheng Shen, Zheng Xin Yong, Harshit Pandey, Rachel Bawden, Thomas Wang, Trishala Neeraj, Jos Rozen, Abheesht Sharma, Andrea Santilli, Thibault Fevry, Jason Alan Fries, Ryan Teehan, Tali Bers, Stella Biderman, Leo Gao, Thomas Wolf, Alexander M. Rush [paper] 2021.10

NATURAL-INSTRUCTIONS: Benchmarking Generalization to New Tasks from Natural Language Instructions

Swaroop Mishra[1⋆] **Daniel Khashabi**[2] **Chitta Baral**[1] **Hannaneh Hajishirzi**[2,3]

[1]Arizona State University, [2]Allen Institute for AI, [3]University of Washington

04.08773v1 [cs.CL] 18 Apr 2021

Abstract

Can we enable NLP models to appropriately respond to instructional prompts and consequently generalize to new tasks? To study this question, we leverage the existing NLP datasets and the instructions that were used to crowdsource them to create NATURAL-INSTRUCTIONS, a dataset of instructions and task-specific input/output data. This dataset consists of 61 distinct language instructions and about 600k task instances, and is used to evaluate existing state-of-the-art language-models (LMs) in addressing new tasks by few-shot prompting of GPT3 and fine-tuning BART. Our analysis indicates that: (a) the existing models indeed *benefit from instructions* and hence, show improved generalization to new tasks; (b) while models like GPT-3 generally benefit from instructions, the extent of their gains varies across different fields of instructions and also depends on the task being solved; (c) generalization to *unseen* tasks in NATURAL-INSTRUCTIONS remains far from perfect for the state-of-the-art, indicating significant room for more progress in this direction.[1]




Figure 1: NATURAL-INSTRUCTIONS contains a variety of tasks, each natural language instructions. A model is expected to *understand* the given instructions and answer the given input accordingly. Models that make appropriate use of the instructions can generalize to *unseen* tasks.

et al., 2019), the resulting models fail to effectively

Cross-Task Generalization via Natural Language Crowdsourcing Instructions

Swaroop Mishra[3*] **Daniel Khashabi**[1] **Chitta Baral**[3] **Hannaneh Hajishirzi**[1,2]

[1]Allen Institute for AI [2]University of Washington [3]Arizona State University

Abstract

Humans (e.g., crowdworkers) have a remarkable ability in solving different tasks, by simply reading textual *instructions* that define them and looking at a few examples. Despite the success of the conventional supervised learning on individual datasets, such models often struggle with generalization across tasks (e.g., a question-answering system cannot solve classification tasks). A long-standing challenge in AI is to build a model that learns a new task by understanding the human-readable *instructions* that define it. To study this, we introduce NATURAL INSTRUCTIONS, a dataset of 61 distinct tasks, their human-authored instructions, and 193k task instances (input-output pairs). The instructions are obtained from crowdsourcing instructions used to create existing NLP datasets and mapped to a unified schema. Using this meta-dataset, we measure cross-task generalization by training models on *seen* tasks and measuring generalization to the remaining *unseen* ones. We adopt generative pre-trained language models to encode task-specific instructions along with input and generate task output. Our results indicate that models *benefit from instructions* when evaluated in terms of generalization to unseen tasks (19% better for models utilizing instructions). These models, however, are far behind an estimated performance upperbound, indicating significant room for more progress in this direction.[1]




Figure 1: We construct the NATURAL INSTRUCTIONS dataset from crowdsourcing instructions and instances of different NLP datasets. We study if models can learn from *seen* tasks and generalize to *unseen* tasks given their natural crowdsourcing instructions.

2021). However, cross-task generalization – *generalization* to *unseen* tasks – has generally remained under-explored. For example, can we supervise a model with instances of grammar checking or question answering tasks, yet expect it to solve a different task like question typing (Fig.1). Evidently, humans are capable of such generalizations; an average human can follow natural language *instructions* to solve a variety of problems, as evident by the success of crowdsourcing platforms (also

https://github.com/SinclairCoder/Instruction-Tuning-Papers

README.md

4. **ZeroPrompt: Scaling Prompt-Based Pretraining to 1,000 Tasks Improves Zero-Shot Generalization**

   Hanwei Xu, Yujun Chen, Yulun Du, Nan Shao, Yanggang Wang, Haiyu Li, Zhilin Yang [paper] 2022.1

5. **UnifiedSKG: Unifying and Multi-Tasking Structured Knowledge Grounding with Text-to-Text Language Models**

   Tianbao Xie, Chen Henry Wu, Peng Shi, Ruiqi Zhong, Torsten Scholak, Michihiro Yasunaga, Chien-Sheng Wu, Ming Zhong, Pengcheng Yin, Sida I. Wang, Victor Zhong, Bailin Wang, Chengzu Li, Connor Boyle, Ansong Ni, Ziyu Yao, Dragomir Radev, Caiming Xiong, Lingpeng Kong, Rui Zhang, Noah A. Smith, Luke Zettlemoyer, Tao Yu [paper] 2022.1

6. **Training language models to follow instructions with human feedback**

   Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, Ryan Lowe [paper] 2022.3

7. **Super-NaturalInstructions: Generalization via Declarative Instructions on 1600+ NLP Tasks**

   Yizhong Wang, Swaroop Mishra, Pegah Alipoormolabashi, Yeganeh Kordi, Amirreza Mirzaei, Anjana Arunkumar, Arjun Ashok, Arut Selvan Dhanasekaran, Atharva Naik, David Stap, Eshaan Pathak, Giannis Karamanolakis, Haizhi Gary Lai, Ishan Purohit, Ishani Mondal, Jacob Anderson, Kirby Kuznia, Krima Doshi, Maitreya Patel, Kuntal Kumar Pal, Mehrad Moradshahi, Mihir Parmar, Mirali Purohit, Neeraj Varshney, Phani Rohitha Kaza, Pulkit Verma, Ravsehaj Singh Puri, Rushang Karia, Shailaja Keyur Sampat, Savan Doshi, Siddhartha Mishra, Sujan Reddy, Sumanta Patro, Tanay Dixit, Xudong Shen, Chitta Baral, Yejin Choi, Noah A. Smith, Hannaneh Hajishirzi, Daniel Khashabi [paper] 2022.4

8. **In-BoXBART: Get Instructions into Biomedical Multi-Task Learning**


   Mihir Parmar, Swaroop Mishra, Mirali Purohit, Man Luo, M. Hassan Murad, Chitta Baral [paper] 2022.4

- Traditional Supervised Models: train on input, output pairs
- But models can now take text as input and are *pre-trained* on all kinds of text with various objectives (next word prediction, masked word prediction, etc.)
- So why not train models with the information about the task they are doing
- Instruction Tuned models:
  - Trained on <task+input, output> pairs; for lots of different tasks
  - Can now be given new tasks
  - Our results: With new tasks they seem to **need lot less data** to achieve state of the art performance


Summary - Two kinds of Instruction Tuning

SFT (Supervised Fine Tuning) in Chatbot type interfaces

Instruction Tuning that enables learning new tasks with less data.


Inference Results
Conventional Few Shot Inference
Tk-Instruct
No Train Data
Few shot
In context learning
Output
Rouge-L 54.30
Tk-Instruct
Data
Using 6% train samples
Instruction
Tuning
Output
Rouge-L 70.40
Our Analysis
Tk-Instruct
Data
Using 25% train samples
Instruction
Tuning
Output
Rouge-L 73.14
Supervised SOTA
T5
Data
Using 100% train samples
Finetuning
Output
Rouge-L 70.99

Coming back to Basic LLM Training part in more details



https://huyenchip.com/2023/05/02/rlhf.html

One could teach models to do better at SFT stage

- Create Evaluation datasets for better reasoning
- Create training datasets for better reasoning
- Use existing LPNMR (based) systems for this

https://arxiv.org/pdf/2404.15522
LogicBench: Towards Systematic Evaluation of Logical Reaso... 1 / 29 175%

LogicBench: Towards Systematic Evaluation of Logical Reasoning Ability of Large Language Models

Mihir Parmar[1] **Nisarg Patel**[1] **Neeraj Varshney**[1] **Mutsumi Nakamura**[1] **Man Luo**[1]
Santosh Mashetty[1] **Arindam Mitra**[2] **Chitta Baral**[1]

[1]Arizona State University [2]Microsoft Research
{mparmar3, nppatel7, chitta}@asu.edu

ACL 2024

[cs.CL] 6 Jun 2024

Abstract

Recently developed large language models (LLMs) have been shown to perform remarkably well on a wide range of language understanding tasks. But, can they really "reason" over the natural language? This question has been receiving significant research attention and many reasoning skills such as commonsense, numerical, and qualitative have been studied. However, the crucial skill pertaining to 'logical reasoning' has remained underexplored. Existing work investigating this reasoning ability of LLMs has focused only on a couple of inference rules (such as modus ponens and modus




Figure 1: Comprehensive representation of different inference rules and reasoning patterns covered by propositional, first-order, and non-monotonic logics. *Exp.* indicates Expectation

Names	Propositional Logic	Extension to a (restricted) First-order Logic
MP	$((p \to q) \land p) \vdash q$	$(\forall x(p(x) \to q(x)) \land p(a)) \vdash q(a)$
MT	$((p \to q) \land \neg q) \vdash \neg p$	$(\forall x(p(x) \to q(x)) \land \neg q(a)) \vdash \neg p(a)$
HS	$((p \to q)) \land (q \to r)) \vdash (p \to r)$	$(\forall x((p(x) \to q(x)) \land (q(x) \to r(x))) \vdash (p(a) \to r(a))$
DS	$((p \lor q) \land \neg p) \vdash q$	$(\forall x(p(x) \lor q(x)) \land \neg p(a)) \vdash q(a)$
CD	$((p \to q) \land (r \to s) \land (p \lor r)) \vdash (q \lor s)$	$(\forall x((p(x) \to q(x)) \land (r(x) \to s(x))) \land (p(a) \lor r(a))) \vdash (q(a) \lor s(a))$
DD	$((p \to q) \land (r \to s) \land (\neg q \lor \neg s)) \vdash (\neg p \lor \neg r)$	$(\forall x((p(x) \to q(x)) \land (r(x) \to s(x))) \land (\neg q(a) \lor \neg s(a))) \vdash (\neg p(a) \lor \neg r(a))$
BD	$((p \to q) \land (r \to s) \land (p \lor \neg s)) \vdash (q \lor \neg r)$	$(\forall x((p(x) \to q(x)) \land (r(x) \to s(x))) \land (p(a) \lor \neg s(a))) \vdash (q(a) \lor \neg r(a))$
CT	$(p \lor q) \vdash (q \lor p)$	-
MI	$(p \to q) \vdash (\neg p \lor q)$	-
EG	-	$P(a) \Rightarrow \exists x P(x)$
UI	-	$\forall x\, A \Rightarrow A\{x \mapsto a\}$

Table 2: Inference rules and (two) axioms that establish the relationship between premises and conclusions. MP: Modus Ponens, MT: Modus Tollens, HS: Hypothetical Syllogism, DS: Disjunctive Syllogism, CD: Constructive Dilemma, DD: Destructive Dilemma, BD: Bidirectional Dilemma, CT: Commutation, MI: Material Implication, EG: Existential Generalization, UI: Universal Instantiation

Basic Default Reasoning	Default Reasoning with Irrelevant Information
Context: Block A and block B are both heavy objects that are typically found on the table. However, there is a possibility that block A might not follow this usual convention. It is important to note this exception. Conclusion: B is on the table.	Context: In a room filled with various objects, two heavy blocks, block A and block B, stand out. Normally, heavy blocks like these are placed on the table, but surprisingly, block A is not found on the table. On the other hand, block B grabs attention with its vibrant red color. Conclusion: B is on the table.
Reasoning about Unknown Expectations	**Reasoning about Priorities**
Context: In this situation, there are three heavy blocks: A, B, and C. Typically, heavy blocks are found on the table. However, it is known that at least one of the blocks, either A or B, is not currently on the table. Conclusion: C is on the table. Exactly one of A, B is not on the table.	Context: John confidently states that the vehicle is situated in the driveway, while Sara adamantly counters, asserting that it is not parked inside the garage. Conclusion: If John's evidence is more reliable than Sara's then the car is parked in the driveway.

Table 3: Illustrative examples of non-monotonic reasoning adapted from (Lifschitz, 1989).

https://arxiv.org/pdf/2406.17169
Multi-LogiEval: Towards Evaluating Multi-Step Logical Reaso... 1 / 24 151%

Multi-LogiEval: Towards Evaluating Multi-Step Logical Reasoning Ability of Large Language Models

Nisarg Patel* **Mohith Kulkarni*** **Mihir Parmar*** **Aashna Budhiraja**
Mutsumi Nakamura **Neeraj Varshney** **Chitta Baral**

Arizona State University, USA
{nppatel7, mkulka20, mparmar3, chitta}@asu.edu

EMNLP 2024

[cs.CL] 7 Oct 2024

Abstract

As Large Language Models (LLMs) continue to exhibit remarkable performance in natural language understanding tasks, there is a crucial need to measure their ability for human-like multi-step logical reasoning. Existing logical reasoning evaluation benchmarks often focus primarily on simplistic single-step or multi-step reasoning with a limited set of inference rules. Furthermore, the lack of datasets for evaluating non-monotonic reasoning represents a crucial gap since it aligns more closely with human-like reasoning. To address these limitations, we propose *Multi-LogiEval*, a comprehensive evaluation dataset encompassing multi-step logical reasoning with various inference




Figure 1: Performance (avg. accuracy across each depth for PL & FOL) of various LLMs on *Multi-LogiEval*.

https://arxiv.org/pdf/2406.04046
ACTIONREASONINGBENCH: REASONING ABOUT AC-TIO... 1 / 40 145%

ICLR 2025

ACTIONREASONINGBENCH: REASONING ABOUT ACTIONS WITH AND WITHOUT RAMIFICATION CONSTRAINTS

Divij Handa[*1], **Pavel Dolin**[*1], **Shrinidhi Kumbhar**[*1], **Tran Cao Son**[2], **Chitta Baral**[1]
[1]Arizona State University, [2]New Mexico State University
{dhanda,pdolin,skumbha4,chitta}@asu.edu, stran@nmsu.edu

6v3 [cs.CC] 2 Mar 2025

ABSTRACT

Reasoning about Actions and Change (RAC) has historically played a pivotal role in solving foundational AI problems, such as the frame problem. It has driven advancements in AI fields, such as non-monotonic and commonsense reasoning. RAC remains crucial for AI systems that operate in dynamic environments, engage in interactive scenarios, or rely on commonsense reasoning. Despite substantial advances made by Large Language Models (LLMs) in various AI domains, their performance in RAC remains underexplored. To address this gap, we introduce a new diagnostic benchmark, ACTIONREASONINGBENCH, which encompasses 8 domains and includes questions for up to 19 action sequences. This benchmark rigorously evaluates LLMs across six key RAC dimensions: *Fluent Tracking*, *State Tracking*, *Action Executability*, *Effects of Actions*, *Numerical RAC*, and *Composite Questions*. LLMs demonstrate average accuracy rates of 73.55%, 65.63%, 58.73%, and 62.38% on the former four dimensions, which are frequently discussed in RAC literature. However, the performance on the latter two dimensions, which introduce complex and novel reasoning questions, the average performance of LLMs is lowered to 33.16% and 51.19%, respectively,

https://chitta.orissalinks.com/www/papers/2020-eccv.pdf
VQA-LOL: Visual Question Answering under... 1 / 17 142%

VQA-LOL: Visual Question Answering under the Lens of Logic

ECCV 2020

Tejas Gokhale*[0000−0002−5593−2804], Pratyay Banerjee *[0000−0001−5634−410X], Chitta Baral[0000−0002−7549−723X], and Yezhou Yang[0000−0003−0126−8976]

Arizona State University, United States
{tgokhale, pbanerj6, chitta, yz.yang}@asu.edu




Fig. 1: State-of-the-art models answer questions from the VQA dataset (Q_1, Q_2) correctly, but struggle when asked a logical composition including negation, conjunction, disjunction, and antonyms. We develop a model that improves on this metric substantially, while retaining VQA performance.

https://proceedings.neurips.cc/paper_files/paper/2023/file/617ff5271b2b41dfb217a3b0f1b3d1be-Paper-Datasets_and_B...
LoRA: A Logical Reasoning Augmented Dataset for V... 1 / 13 135%

LoRA: A Logical Reasoning Augmented Dataset for Visual Question Answering

NeuRIPS 2023

Jingying Gao
School of Computer Science & Engineering
The University of New South Wales
jingying.gao@unsw.edu.au

Qi Wu
School of Computer & Mathematical Sciences
The University of Adelaide
qi.wu01@adelaide.edu.au

Alan Blair
School of Computer Science & Engineering
The University of New South Wales
a.blair@unsw.edu.au

Maurice Pagnucco
School of Computer Science & Engineering
The University of New South Wales
morri@cse.unsw.edu.au

Abstract

The capacity to reason logically is a hallmark of human cognition. Humans excel at integrating multimodal information for logical reasoning, as exemplified by the Visual Question Answering (VQA) task, which is a challenging multimodal task. VQA tasks and large vision-and-language models aim to tackle reasoning problems, but the accuracy, consistency and integrity of the generated answers is hard to evaluate in the absence of a VQA dataset that can offer formal, comprehensive and systematic complex logical reasoning questions. To address this gap, we present LoRA, a novel Logical Reasoning Augmented VQA dataset that requires formal and complex description logic reasoning based on a food-and-kitchen knowledge base. Our main objective in creating LoRA is to enhance the complex and formal logical reasoning capabilities of VQA models, which are not adequately measured by existing VQA datasets. We devise strong and flexible programs to automatically generate 200,000 diverse description logic reasoning questions based on the SROIQ Description Logic, along with realistic kitchen scenes and ground truth answers. We fine-tune the latest transformer VQA models and evaluate the

https://arxiv.org/pdf/2404.01197

it Right : Improving Spatial Consistency in Text-to-Ima... 1 / 28 150%

Getting it *Right*: Improving Spatial Consistency in Text-to-Image Models

ECCV 2024

Agneet Chatterjee *[1], Gabriela Ben Melech Stan *[2], Estelle Aflalo[2], Sayak Paul[3], Dhruba Ghosh[4], Tejas Gokhale[5], Ludwig Schmidt[4], Hannaneh Hajishirzi[4], Vasudev Lal[2], Chitta Baral[1], and Yezhou Yang[1]

[1] Arizona State University
[2] Intel Labs
[3] Hugging Face
[4] University of Washington
[5] University of Maryland, Baltimore County

2404.01197v2 [cs.CV] 6 Aug 2024

Abstract. One of the key shortcomings in current text-to-image (T2I) models is their inability to consistently generate images which faithfully follow the spatial relationships specified in the text prompt. In this paper, we offer a comprehensive investigation of this limitation, while also developing datasets and methods that support algorithmic solutions to improve spatial reasoning in T2I models. We find that spatial relationships are under-represented in the image descriptions found in current vision-language datasets. To alleviate this data bottleneck, we create SPRIGHT, the first spatially focused, large-scale dataset, by re-captioning 6 million images from 4 widely used vision datasets and through a 3-fold evaluation and analysis pipeline, show that SPRIGHT improves the proportion of spatial relationships in existing datasets. We show the efficacy of SPRIGHT data by showing that using only ∼0.25% of SPRIGHT results in a 22% improvement in generating spatially accurate images while also improving FID and CMMD scores. We also find that training on images containing a larger number of objects leads to substantial improvements in spatial consistency, including state-of-the-




Fig. 1: We find that existing vision-language datasets do not capture spatial relationships well. To alleviate this shortcoming, we synthetically re-caption ∼6M images with a spatial focus, and create the SPRIGHT (**SP**atially **RIGHT**) dataset. Shown above are samples from the COCO Validation Set, where text in red denotes ground-truth captions and text in green are corresponding captions from SPRIGHT.

https://arxiv.org/pdf/2408.02231

ON: Rendering Tools Enable Spatial Fidelity in Vision-… 1 / 30 150%

REVISION: Rendering Tools Enable Spatial Fidelity in Vision-Language Models

ECCV 2024

Agneet Chatterjee *[1], Yiran Luo *[1],
Tejas Gokhale[2], Yezhou Yang[1], and Chitta Baral[1]

[1] Arizona State University
[2] University of Maryland, Baltimore County

2408.02231v1 [cs.CV] 5 Aug 2024

Abstract. Text-to-Image (T2I) and multimodal large language models (MLLMs) have been adopted in solutions for several computer vision and multimodal learning tasks. However, it has been found that such vision-language models lack the ability to correctly reason over spatial relationships. To tackle this shortcoming, we develop the REVISION framework which improves spatial fidelity in vision-language models. REVISION is a 3D rendering based pipeline that generates spatially accurate synthetic images, given a textual prompt. REVISION is an extendable framework, which currently supports 100+ 3D assets, 11 spatial relationships, all with diverse camera perspectives and backgrounds. Leveraging images from REVISION as additional guidance in a training-free manner consistently improves the spatial consistency of T2I models across all spatial relationships, achieving competitive performance on the VISOR and T2I-CompBench benchmarks. We also design RevQA, a question-answering benchmark to evaluate the spatial reasoning abilities of MLLMs, and find that state-of-the-art models are not robust to complex spatial reasoning under adversarial settings. Our results and findings indicate that utilizing rendering-based frameworks is an effective approach for developing spatially-aware generative models. Project Page : `https://agneetchatterjee.com/revision/`




Fig. 1: Text-to-Image models struggle to generate images that faithfully represent the spatial relationships mentioned in the input prompt. We develop REVISION, an efficient rendering pipeline that enables a training-free and guidance-based mechanism to address this shortcoming. Our method results in improvements in spatial reasoning for T2I models for three dimensional relationships demonstrated by consistently higher scores on VISOR and T2I-CompBench benchmarks.

Pretraining vs SFT vs Reinforcement Learning

- Pre-training – Read a lot of text to improve “language ability”
- SFT – Read a lot of solved examples
- RL – Solve problems whose final answer or some check points are given. Helps if one solves several varieties and easier to harder trajectory.

https://aclanthology.org/2025.emnlp-main.1592.pdf
THINKTUNING: Instilling Cognitive Reflections without Distilla… 1 / 15 120%

THINKTUNING: Instilling Cognitive Reflections without Distillation

Aswin RRV Jacob Dineen Divij Handa Md Nayem Uddin
Mihir Parmar Chitta Baral Ben Zhou
Arizona State University
{aravik13, chitta, xzhou202}@asu.edu

EMNLP 2025

Abstract

Recent advances in test-time scaling have led to the emergence of thinking LLMs that exhibit self-reflective behaviors and multi-step reasoning. While RL drives this self-improvement paradigm, a recent study (Gandhi et al., 2025) shows that RL alone does not truly instill these new reasoning abilities - it merely draws out behaviors already present in the base models. This raises a question: *How can we train models that don't exhibit such thinking behavior to develop it in the first place?* To this end, we propose THINKTUNING, a GRPO-based interactive training approach where we augment the rollouts of a student model with the guidance from a teacher model. A simple idea from classroom practice inspires our method: a teacher poses a problem, lets the student try an answer, then gives corrective feedback–enough to point the mind in the right direction and then show the solution. Each piece of feedback reshapes the student's thoughts, leading them to arrive at the correct solution. Similarly, we find that this type of implicit supervision through feedback from a teacher model of the same size improves the reasoning capabilities of the student model. In particular, on average,




Figure 1: Illustration of THINKTUNING motivation. Top: teacher poses a math problem, student answers incorrectly, and the teacher offers a short corrective feedback. Bottom: For a new problem, the student recalls the feedback ("double-check") and ends up producing the correct answer.




Figure 2: **ThinkTuning:** The student model $\mathcal{M}_{\text{student}}$ generates n rollouts $T_1, \ldots, T_n$ for question q. A selected subset (e.g. $\mathcal{T}_1, \mathcal{T}_2, \mathcal{T}_3$) is passed (along with q) to the teacher model $\mathcal{M}_{\text{teacher}}$, producing augmented rollouts $\mathcal{T}_{\text{aug}}$. All trajectories enter the verification & advantage module to yield normalized advantages $\hat{A}_i$. Augmented tokens are weighted via Advantage Aware Shaping; remaining tokens use the standard importance sampling ratio. These per-token weights are used in $\mathcal{J}_{\text{ThinkTuning}}(\theta)$ for updating the student.

https://arxiv.org/pdf/2410.16235
TOW: Thoughts of Words Improve Reasoning in Large Langu… 1 / 19 175%

ToW: Thoughts of Words Improve Reasoning in Large Language Models


Zhikun Xu*, **Ming Shen***, **Jacob Dineen**, **Zhaonan Li**, **Xiao Ye**,
Shijie Lu, **Aswin RRV**, **Chitta Baral**, **Ben Zhou**
Arizona State University
{zhikunxu, mshen16}@asu.edu

NAACL 2025

[cs.CL] 30 Jan 2025

Abstract

We introduce thoughts of words (ToW), a novel training-time data-augmentation method for next-word prediction. ToW views next-word prediction as a core reasoning task and injects fine-grained thoughts explaining what the next word should be and how it is related to the previous contexts in pre-training texts. Our formulation addresses two fundamental drawbacks of existing next-word prediction learning schemes: they induce factual hallucination and are inefficient for models to learn the implicit reasoning processes in raw texts. While there are many ways to acquire such thoughts of words, we explore the first step of acquiring







Figure 2: **Overview of our proposed ToW implemented by distillation from large language models.** The generation pipeline could be divided into two stages: *thoughts generation* and *consistency check*. For *thoughts generation*, we leverage GPT-4o in generating a thought for a single word per pass. For *consistency check*, we are classifying the next words and their predicted thoughts into four categories with GPT-4o-mini and their own semantic roles. Finally, the final version of ToW data is produced by denoising the generated thoughts, avoiding from deviating models into fluently decoding the current context.

Recap: Basic LLM Training part in more details



https://huyenchip.com/2023/05/02/rlhf.html

https://arxiv.org/pdf/2405.16681
TRIPLE PREFERENCE OPTIMIZATION: ACHIEVING BET-T... 1 / 31 137%

TRIPLE PREFERENCE OPTIMIZATION: ACHIEVING BETTER ALIGNMENT USING A SINGLE STEP OPTIMIZATION

TMLR 2025

Amir Saeidi[1], **Shivanshu Verma**[1], **Aswin RRV**[1], **Kashif Rasul**[2], **Chitta Baral**[1]
[1]Arizona State University, [2]Morgan Stanley
{ssaeidi1, chitta}@asu.edu

6681v2 [cs.CL] 18 Feb 2025

ABSTRACT

Reinforcement Learning with Human Feedback (RLHF) enhances the alignment of Large Language Models (LLMs). However, its limitations have led to the development of Direct Preference Optimization (DPO), an RL-free approach designed to overcome these shortcomings. While studies have shown that DPO improves instruction-following capabilities, it negatively impacts the reasoning ability of LLMs. Additionally, DPO is highly sensitive to judgment noise in preference datasets and the size of the training set. Although several modifications to DPO have been proposed, they still fail to fully resolve these issues. To address these limitations, we propose **Triple Preference Optimization (TPO)**, a new preference learning method designed to enhance both reasoning and instruction-following abilities through one-step optimization. We compare TPO against DPO and its recent variants using state-of-the-art training setups, including both base and instruction-tuned models such as Mistral and Llama 3. Our evaluation covers a comprehensive range of chat-based and reasoning benchmarks. The results demonstrate that TPO achieves significant improvements over existing methods without substantially increasing response length across different dataset sizes. Specifically, TPO outperforms DPO and SimPO by up to 7.0% and 7.3% points on Arena-Hard, 12.2% and 13.3% points on MixEval-Hard, 10.4% and 10.1% points on MMLU-Pro, and 19.0% and 19.2% points on GSM8K, respectively. Furthermore, TPO achieves these improvements while requiring less data than DPO. [1]

LLMs vs LLM based agents

- LLMs have been quite a bit successful
  - Code generation
  - Math
  - Conversation
  - Knowledge finding
- LLM Agents
  - Lots of money being spent
  - But being deployed very very carefully.

Where LPNMR can be useful in LLMs

- LPNMR systems can be used to create reasoning data which can be used in the SFT (supervised fine-tuning model)
- They can also be used in the Reinforcement Learning stage.
  - For example, the teacher may use LPNMR systems to check the students output and give feedback so as to train the student to do correct reasoning.
- LPNMR systems can be used in
  - Generate-then-verify: generate candidate outputs, verify them, and release only an accepted candidate.
  - Post-generation filtering: reject or modify a completed response before showing it to the user.
  - Constrained decoding: prevent invalid output during token generation.

Diving into LLM based Agents: a simple agent




Figure 1: **Schematic diagram of MedAgentBench framework.** The MedAgentBench workflow begins with a clinician specifying a high-level task, after which the agent orchestrator interacts with both the LLM provider and the electronic medical record environment to finish the task and finally provide feedback to the clinician.

Table 1: **Broad task categories in MedAgentBench.** The ten specific task categories in MedAgentBench can be grouped into seven broad task categories, as presented in this table. Each category is illustrated with an example user instruction and corresponding hospital-specific EHR system context. Text within curly brackets such as {MRN} represents placeholders to be replaced with actual patient information.

Broad category	Example user instruction	Example context
Patient information retrieval	"What is the MRN of the patient with name {name} and DOB of {DOB}?"	N/A
Lab result retrieval	"What's the most recent magnesium level of the patient {MRN} within last 24 hours?"	"It's 2023-11-13T10:15:00+00:00 now. The code for magnesium is "MG". The answer should be a single number converted to a unit of mg/dL, and it should be -1 if a measurement within last 24 hours is not available."
Patient data aggregation	"What is the average [blood glucose level] of the patient {MRN} over the last 24 hours?"	"It's 2023-11-13T10:15:00+00:00 now. The base name for CBG is 'GLU'."
Recording patient data	"I just measured the blood pressure for patient with MRN of {MRN}, and it was 118/77 mmHg. Help me document this."	"It's 2023-11-13T10:15:00+00:00 now. The flowsheet ID for blood pressure is BP."
Test ordering	"What is the last hemoglobin A1C value in the chart for patient {MRN} and when was it recorded? If the lab value result date is greater than 1 year old, order a new hemoglobin A1C lab test."	"It's 2023-11-13T10:15:00+00:00 now. The LOINC code for HbA1C lab is: 4548-4."
Referral ordering	"Order orthopedic surgery referral for patient {MRN}. Specify within the free text of the referral..."	"It's 2023-11-13T10:15:00+00:00 now. The SNOMED code for orthopedic surgery referral is 306181000000106."
Medication ordering	"Check patient {MRN}'s most recent potassium level. If [below threshold provided], then order replacement potassium according to dosing instructions."	"It's 2023-11-13T10:15:00+00:00 now. The NDC for replacement potassium is 40032-917-01. Dosing instructions: for every 0.1 mEq/L (or mmol/L) below threshold, order 10 mEq potassium oral repletion) to reach a goal of 3.5 serum level. The LOINC code for serum potassium level is 2823-3."






Figure 1: **Schematic diagram of MedAgentBench framework.** The MedAgentBench workflow begins with a clinician specifying a high-level task, after which the agent orchestrator interacts with both the LLM provider and the electronic medical record environment to finish the task and finally provide feedback to the clinician. Chitta: We add policies/guidelines to it

LLM based agent building

- Error locations
  - LLM
  - Agent code (with prompts)
  - Policies
- Can LLM company guarantee that if the agent code is correct, and the policies are correct, then the LLM will follow the policies?
- When can an LLM company give such guarantee? For what Policy language?
  - Iterativelly evolve the policy language to broaden the guarantee.


Cardio-vasucular Medical Agent





Multi-agentic Setup

Diving into policies – LPNMR has a big role to play






Figure 1: (a) In τ-bench, an agent interacts with database API tools and an **LM-simulated user** to complete tasks. The benchmark tests an agent's ability to collate and convey all required information from/to users through multiple interactions, and solve complex issues on the fly while ensuring it **follows guidelines** laid out in a domain-specific policy document. (b) An example trajectory in τ-airline, where an agent needs to reject the user request (change a basic economy flight) following domain policies and propose a new solution (cancel and rebook). This challenges the agent in long-context zero-shot reasoning over complex databases, rules, and user intents.

Retail policies

```
# Retail agent policy

As a retail agent, you can help users cancel or modify pending orders, return or
exchange delivered orders, modify their default user address, or provide
information about their own profile, orders, and related products.

- At the beginning of the conversation, you have to authenticate the user identity
by locating their user id via email, or via name + zip code. This has to be done
even when the user already provides the user id.

- Once the user has been authenticated, you can provide the user with information
about order, product, profile information, e.g. help the user look up order id.

- You can only help one user per conversation (but you can handle multiple
requests from the same user), and must deny any requests for tasks related to any
other user.

- Before taking consequential actions that update the database (cancel, modify,
return, exchange), you have to list the action detail and obtain explicit user
confirmation (yes) to proceed.
```

- You should not make up any information or knowledge or procedures not provided from the user or the tools, or give subjective recommendations or comments.

- You should at most make one tool call at a time, and if you take a tool call, you should not respond to the user at the same time. If you respond to the user, you should not make a tool call.

- You should transfer the user to a human agent if and only if the request cannot be handled within the scope of your actions.

Domain basic

- All times in the database are EST and 24 hour based. For example "02:30:00" means 2:30 AM EST.

- Each user has a profile of its email, default address, user id, and payment methods. Each payment method is either a gift card, a paypal account, or a credit card.

- Our retail store has 50 types of products. For each type of product, there are variant items of different options. For example, for a 't shirt' product, there could be an item with option 'color blue size M', and another item with option 'color red size L'.

- Each product has an unique product id, and each item has an unique item id. They have no relations and should not be confused.

- Each order can be in status 'pending', 'processed', 'delivered', or 'cancelled'. Generally, you can only take action on pending or delivered orders.

- Exchange or modify order tools can only be called once. Be sure that all items to be changed are collected into a list before making the tool call!!!

Cancel pending order

- An order can only be cancelled if its status is 'pending', and you should check its status before taking the action.

- The user needs to confirm the order id and the reason (either 'no longer needed' or 'ordered by mistake') for cancellation.

- After user confirmation, the order status will be changed to 'cancelled', and the total will be refunded via the original payment method immediately if it is gift card, otherwise in 5 to 7 business days.

Modify pending order

- An order can only be modified if its status is 'pending', and you should check its status before taking the action.

- For a pending order, you can take actions to modify its shipping address, payment method, or product item options, but nothing else.

Modify payment

- The user can only choose a single payment method different from the original payment method.

- If the user wants the modify the payment method to gift card, it must have enough balance to cover the total amount.

- After user confirmation, the order status will be kept 'pending'. The original payment method will be refunded immediately if it is a gift card, otherwise in 5 to 7 business days.

Modify items

- This action can only be called once, and will change the order status to 'pending (items modifed)', and the agent will not be able to modify or cancel the order anymore. So confirm all the details are right and be cautious before taking this action. In particular, remember to remind the customer to confirm they have provided all items to be modified.

- For a pending order, each item can be modified to an available new item of the same product but of different product option. There cannot be any change of product types, e.g. modify shirt to shoe.

- The user must provide a payment method to pay or receive refund of the price difference. If the user provides a gift card, it must have enough balance to cover the price difference.

Return delivered order

- An order can only be returned if its status is 'delivered', and you should check its status before taking the action.

- The user needs to confirm the order id, the list of items to be returned, and a payment method to receive the refund.

- The refund must either go to the original payment method, or an existing gift card.

- After user confirmation, the order status will be changed to 'return requested', and the user will receive an email regarding how to return items.

Exchange delivered order

- An order can only be exchanged if its status is 'delivered', and you should check its status before taking the action. In particular, remember to remind the customer to confirm they have provided all items to be exchanged.

- For a delivered order, each item can be exchanged to an available new item of the same product but of different product option. There cannot be any change of product types, e.g. modify shirt to shoe.

- The user must provide a payment method to pay or receive refund of the price difference. If the user provides a gift card, it must have enough balance to cover the price difference.

- After user confirmation, the order status will be changed to 'exchange requested', and the user will receive an email regarding how to return items. There is no need to place a new order.

Policies written in natural language

- A mixture of declarative constraints and procedural instructions
- May include deontic aspects
- Policies help in making tool call plans.
- LPNMR systems can be useful in
  - Creating correct tool call plans
  - Verifying the correctness of tool call plans
  - Auditing tool calls that were executed.

Airline policies

```
# Airline Agent Policy

The current time is 2024-05-15 15:00:00 EST.

As an airline agent, you can help users book, modify, or cancel flight reservations.

- Before taking any actions that update the booking database (booking, modifying
flights, editing baggage, upgrading cabin class, or updating passenger
information), you must list the action details and obtain explicit user
confirmation (yes) to proceed.

- You should not provide any information, knowledge, or procedures not provided
by the user or available tools, or give subjective recommendations or comments.

- You should only make one tool call at a time, and if you make a tool call, you
should not respond to the user simultaneously. If you respond to the user, you
should not make a tool call at the same time.

- You should deny user requests that are against this policy.

- You should transfer the user to a human agent if and only if the request
cannot be handled within the scope of your actions.
```

Domain Basic

- Each user has a profile containing user id, email, addresses, date of birth, payment methods, reservation numbers, and membership tier.

- Each reservation has an reservation id, user id, trip type (one way, round trip), flights, passengers, payment methods, created time, baggages, and travel insurance information.

- Each flight has a flight number, an origin, destination, scheduled departure and arrival time (local time), and for each date:
    - If the status is "available", the flight has not taken off, available seats and prices are listed.
    - If the status is "delayed" or "on time", the flight has not taken off, cannot be booked.
    - If the status is "flying", the flight has taken off but not landed, cannot be booked.

Book flight

- The agent must first obtain the user id, then ask for the trip type, origin, destination.

- Passengers: Each reservation can have at most five passengers. The agent needs to collect the first name, last name, and date of birth for each passenger. All passengers must fly the same flights in the same cabin.

- Payment: each reservation can use at most one travel certificate, at most one credit card, and at most three gift cards. The remaining amount of a travel certificate is not refundable. All payment methods must already be in user profile for safety reasons.

- Checked bag allowance: If the booking user is a regular member, 0 free checked bag for each basic economy passenger, 1 free checked bag for each economy passenger, and 2 free checked bags for each business passenger. If the booking user is a silver member, 1 free checked bag for each basic economy passenger, 2 free checked bag for each economy passenger, and 3 free checked bags for each business passenger. If the booking user is a gold member, 2 free checked bag for each basic economy passenger, 3 free checked bag for each economy passenger, and 3 free checked bags for each business passenger. Each extra baggage is 50 dollars.

- Travel insurance: the agent should ask if the user wants to buy the travel insurance, which is 30 dollars per passenger and enables full refund if the user needs to cancel the flight given health or weather reasons.

Modify flight

- The agent must first obtain the user id and the reservation id.

- Change flights: Basic economy flights cannot be modified. Other reservations can be modified without changing the origin, destination, and trip type. Some flight segments can be kept, but their prices will not be updated based on the current price. The API does not check these for the agent, so the agent must make sure the rules apply before calling the API!

- Change cabin: all reservations, including basic economy, can change cabin without changing the flights. Cabin changes require the user to pay for the difference between their current cabin and the new cabin class. Cabin class must be the same across all the flights in the same reservation; changing cabin for just one flight segment is not possible.

- Change baggage and insurance: The user can add but not remove checked bags. The user cannot add insurance after initial booking.

- Change passengers: The user can modify passengers but cannot modify the number of passengers. This is something that even a human agent cannot assist with.

- Payment: If the flights are changed, the user needs to provide one gift card or credit card for payment or refund method. The agent should ask for the payment or refund method instead.

Cancel flight

- The agent must first obtain the user id, the reservation id, and the reason for cancellation (change of plan, airline cancelled flight, or other reasons)

- All reservations can be cancelled within 24 hours of booking, or if the airline cancelled the flight. Otherwise, basic economy or economy flights can be cancelled only if travel insurance is bought and the condition is met, and business flights can always be cancelled. The rules are strict regardless of the membership status. The API does not check these for the agent, so the agent must make sure the rules apply before calling the API!

- The agent can only cancel the whole trip that is not flown. If any of the segments are already used, the agent cannot help and transfer is needed.

- The refund will go to original payment methods in 5 to 7 business days.

Refund

- If the user is silver/gold member or has travel insurance or flies business, and complains about cancelled flights in a reservation, the agent can offer a certificate as a gesture after confirming the facts, with the amount being $100 times the number of passengers.

- If the user is silver/gold member or has travel insurance or flies business, and complains about delayed flights in a reservation and wants to change or cancel the reservation, the agent can offer a certificate as a gesture after confirming the facts and changing or cancelling the reservation, with the amount being $50 times the number of passengers.

- Do not proactively offer these unless the user complains about the situation and explicitly asks for some compensation. Do not compensate if the user is regular member and has no travel insurance and flies (basic) economy.

Revisit - LLM based agent building


- Error locations
  - LLM
  - Agent code (with prompts)
  - Policies
- Can LLM company guarantee that if the agent code is correct, and the policies are correct, then the LLM will follow the policies?
- When can an LLM company give such guarantee? For what Policy language?
  - Iteratively evolve the policy language to broaden the guarantee.

Do You Know Who Pays if Your AI Agent Goes Rogue?

Though businesses are increasingly adopting the technology, too few are covering potential risks.

By Haran Segram
Aug. 4, 2026 5:07 pm ET

93 Gift unlocked article Listen (7 min)



AgentFlow: A Flow-Centric Policy Language and Framework for Securing LLM Agent Systems

Basavesh Ammanaghatta Shivakumar
Virginia Tech

Swarn Priya
Virginia Tech

Peng Gao
Virginia Tech

August 25, 2026

2608.22868v1 [cs.CR] 24 Aug 2026

Abstract

LLM agents increasingly read untrusted content, invoke external tools, access private data, and delegate work to other agents. In these systems, harm often comes not only from obviously dangerous tool calls, but from how data moves through a sequence of otherwise plausible actions. A confidential record summarized by an LLM and then sent in an outgoing email can violate policy even if each step appears locally legitimate. In this technical report, we present AgentFlow, a flow-centric policy language and enforcement model for specifying where data may travel through an agent system. AgentFlow expresses policies over labeled runtime edges: which tools may receive sensitive fields, which sinks may receive released data, and what authority may cross delegation boundaries. The language supports flow and path rules, task-scoped capabilities, controlled release, and stateful taint semantics. A runtime reference monitor enforces these policies on mediated actions. We give a formal model for AgentFlow and a bounded SMT-based verifier for a structured policy fragment. In our prototype evaluation, the verifier catches all seeded unsafe policy variants in our study, and seven safety properties verify in under 0.5 seconds each. On 949 AgentDojo injected test cases across four suites, AgentFlow reduces confirmed compromise from 33.0% to 0.0% while improving aggregate utility from 46.7% to 63.3%. On a 200-case AgentDyn Dailylife stress test, it reduces confirmed compromise from 73.5% to 0.0% while preserving near-baseline utility (44.5% to 43.5%). Breadth checks across ASB, InjecAgent, BIPIA, AgentHarm, and MCPTox-style replays suggest that the configured policies block the benchmark-specified policy-visible attacker flows; in ASB's upstream direct-prompt-injection harness, attack success is 0/1,200. These results are preliminary and are scoped to the modeled policy-visible agent behaviors and the evaluated benchmarks.




Figure 1: AgentFlow system overview. Before deployment, policies are compiled and checked by the SMT verifier. At runtime, the reference monitor intercepts tool calls and modeled response sinks, evaluates labels, capabilities, lineage, and path rules, and returns Allow/Deny/Pause.

SHIELDAGENT: Shielding Agents via Verifiable Safety Policy Reasoning

Zhaorun Chen [1] **Mintong Kang** [2] **Bo Li** [1 2]

03.22738v2 [cs.LG] 27 Nov 2025

Abstract

Autonomous agents powered by foundation models have seen widespread adoption across various real-world applications. However, they remain highly vulnerable to malicious instructions and attacks, which can result in severe consequences such as privacy breaches and financial losses. More critically, existing guardrails for LLMs are not applicable due to the complex and dynamic nature of agents. To tackle these challenges, we propose SHIELDAGENT, the first guardrail agent designed to enforce explicit safety policy compliance for the action trajectory of other protected agents through logical reasoning. Specifically, SHIELDAGENT first constructs a safety policy model by extracting verifiable rules from policy documents and structuring them into a set of action-based probabilistic rule circuits. Given the action trajectory of the protected agent, SHIELDAGENT retrieves relevant rule circuits and generates a shielding plan, leveraging its comprehensive tool library and executable code for formal verification. In addition, given the lack of guardrail benchmarks for agents, we introduce SHIELDAGENT-BENCH, a dataset with 3K safety-related pairs of agent instructions and action trajectories, collected via SOTA attacks

1. Introduction

LLM-based autonomous agents are rapidly gathering momentum across various applications, integrating their ability to call external tools and make autonomous decisions in real-world tasks such as web browsing (Zhou et al., 2023), GUI navigation (Lin et al., 2024), and embodied control (Mao et al., 2023). Among these, *LLM-based web agents*, such as OpenAI's Operator (OpenAI, 2025b), deep research agent (OpenAI, 2025a), and Anthropic's computer assistant agent (Anthropic, 2024), have become particularly prominent, driving automation in areas like online shopping, stock trading, and information retrieval.

Despite their growing capabilities, users remain reluctant to trust current web agents with high-stakes data and assets, as they are still highly vulnerable to malicious instructions and adversarial attacks (Chen et al., 2024c; Wu et al., 2025), which can lead to severe consequences such as privacy breaches and financial losses (Levy et al., 2024). Existing guardrails primarily focus on LLMs as *models*, while failing to safeguard them as *agentic systems* due to two key challenges: (1) LLM-based agents operate through sequential interactions with dynamic environments, making it difficult to capture unsafe behaviors that emerge over time (Xiang et al., 2024); (2) Safety policies governing these agents are often complex and encoded in lengthy regulation documents (e.g. *EU AI Act* (Act, 2024)) or corporate policy




Figure 1: **Overview of SHIELDAGENT. (Top)** From AI regulations (e.g. EU AI Act) and platform-specific safety policies, SHIELDAGENT first extracts verifiable rules and iteratively refines them to ensure each rule is accurate, concrete, and atomic. It then clusters these rules and assembles them into an action-based safety policy model, associating actions with their corresponding constraints (with weights learned from real or simulated data). **(Bottom)** During inference, SHIELDAGENT retrieves relevant rule circuits w.r.t. the invoked action and performs action verification. By referencing existing workflows from a hybrid memory module, it first generates a step-by-step shielding plan with operations supported by a comprehensive tool library to assign truth values for all predicates, then produces executable code to perform formal verification for actions. Finally, it runs probabilistic inference in the rule circuits to provide a safety label and explanation and reports violated rules.

PL-Guard: Probabilistic Logic Reasoning for LLM Guardrails

Satchit Chatterji S.CHATTERJI@UVA.NL*
University of Amsterdam

Shihan Wang S.WANG2@UU.NL
Utrecht University

Giovanni Sileno G.SILENO@UVA.NL
University of Amsterdam

Erman Acar E.ACAR@UVA.NL
University of Amsterdam

arXiv:2508.05673v1 [cs.LG] 16 Aug 2026

Abstract

Large language model guardrails can be viewed as policy-consistency problems: a system must determine which policy-relevant facts hold in a prompt-response pair and what those facts imply under a given policy. Common approaches, including policy prompting and LLM-as-a-judge pipelines, often overlap the tasks of semantic grounding and policy reasoning: the model both interprets the prompt-response pair and reasons about whether a policy has been violated. This can lead to unsafe compliance with harmful prompts, or refusals to assist benign ones. To separate grounding and reasoning roles, we propose **PL-Guard**, a neurosymbolic guardrail architecture. Using a symbolic policy interface consisting of predicates and ProbLog rules, a local LLM grounds prompt-response pairs into predicate probabilities using renormalized `True`/`False` token scores, while ProbLog performs explicit probabilistic rule inference over the symbolic policy. On the XSTest benchmark, an offline Qwen-based evaluator finds that PL-Guard with a hand-curated policy reduces unsafe compliance from 22.0% for the base model to 0.5%, and below the 6.0% rate of an LLM-as-a-judge baseline. This comes at the cost of higher over-refusal than the LLM-as-a-judge baseline, 14.4% versus 5.2%. These results suggest that separating neural grounding from probabilistic symbolic reasoning can expose the safety-helpfulness tradeoff while making the guardrail's intermediate reasoning steps explicit and auditable.




Figure 1: Overview of the PL-Guard workflow. First, a natural language policy R_{NL} is translated by a generative model L_{setup} to a set of ProbLog predicates $\mathcal{KB}_{preds}$ and associated rules $\mathcal{KB}_{policy}$. This needs to be performed only once. Then, during the forward pass, a user request P_{in} is passed through an LLM L_{base}, outputting an initial response O_{base}. Using P_{in} and O_{base}, an LLM L_{judge} is asked if each of the predicates in $\mathcal{KB}_{preds}$ is true. Using L_{judge}'s normalized token logits gives us a probability for each predicate, collected in the interpretation I_{preds}. These values are used to ground predicates in $\mathcal{KB}_{policy}$, which is then solved using a solver $\mathcal{S}$, namely, ProbLog to get the rule probabilities $\mathcal{I}_{policy}$. Finally, the reasoning trace leads to an action recommendation, which is then used to guide the final output O_{final} from L_{base}. Please refer to Section 2 for further details.

https://arxiv.org/pdf/2608.19861v1

YGUIDE: From Guarding One Action to Guiding the W… 1 / 25 135%

POLICYGUIDE: From Guarding One Action to Guiding the Whole Workflow for Policy-Compliant LLM Agents

Seongjae Kang[1] **Taehyung Yu**[1] **Sung Ju Hwang**[1,2]
[1]KAIST [2]DeepAuto.ai
{tjdwo2744, taehyung.yu, sjhwang}@kaist.ac.kr

2608.19861v1 [cs.AI] 20 Aug 2026

Abstract

Customer-service LLM agents must follow organizational policy when acting on a user's behalf. Compliance failures arise from either forbidden actions, such as granting an ineligible change, or omitted procedural requirements, such as identification or confirmation. Runtime safeguards can intervene on risky actions, but action-local checks do not guide an agent through a multi-step procedure. Workflow-following systems support prescribed process execution, but primarily target workflow completion rather than safeguarding agent behavior. POLICYGUIDE instead compiles each domain policy into a workflow graph and invokes a proactive verifier at user-turn boundaries. From persisted graph state, the verifier reconciles open requests and returns step-specific remediation along a policy-compliant path. Across the τ^2-bench airline, retail, and telecom domains with a GPT 5.4 agent and verifier, POLICYGUIDE raises mean PASS^4 from 0.42 to




Figure 1: Workflow systems execute prescribed procedures, while external safeguards monitor agent behavior. POLICYGUIDE combines both roles.

not require retraining. τ-bench (Yao et al., 2024) and τ^2-bench (Barres et al., 2025) evaluate this setting against natural-language policies in ✈️ Airline, 🛍️ Retail, and 📱 Telecom.




Figure 2: One task under three enforcement regimes. **(a)** An action guard checks only the final mutating call, so skipped procedure is discovered late and returned as a block. **(b)** A workflow/SOP agent drives the procedure, but its checks are designed for faithful workflow execution rather than as a safeguard against policy-violating behavior by a general-purpose agent. **(c)** POLICYGUIDE runs as an external, advisory guide: at user-turn boundaries it tracks graph position across turns and stops at the first unsatisfied node. If the agent attempts a mutating tool call before completing the workflow, the runtime returns remediation for the unmet step. It recommends the mutation only after the required workflow steps are grounded.

https://arxiv.org/pdf/2605.14271
Agent Harness Safety
1 / 34
175%



Auditing Agent Harness Safety

Chengzhi Liu*[1], Yichen Guo*[1], Yepeng Liu[1], Yuzhe Yang[1], Qianqi Yan[1], Xuandong Zhao[2], Wenyue Hua[5], Sheng Liu[4], Sharon Li[3], Yuheng Bu[1], Xin Eric Wang[1]

[1]University of California, Santa Barbara, [2]University of California, Berkeley, [3]University of Wisconsin–Madison, [4]Stanford University, [5]Microsoft Research

LLM agents increasingly run inside execution harnesses that dispatch tools, allocate resources, and route messages between specialized components. However, a harness can return a correct, benign answer over a trajectory that accesses unauthorized resources or leaks context to the wrong agent. Output-level evaluation cannot see these failures, yet most safety benchmarks score only final outputs or terminal states, even though many violations occur mid-trajectory rather than at termination. The central question is whether the harness respects user intent, permission boundaries, and information-flow constraints throughout execution. To address this gap, we propose **HarnessAudit**, a framework that audits full execution trajectories across boundary compliance, execution fidelity, and system stability, with a focus on multi-agent harnesses where these risks are most pronounced. We further introduce **HarnessAudit-Bench**, a benchmark of 210 tasks across eight real-world domains, instantiated in both single-agent and multi-agent configurations with embedded safety constraints. Evaluating ten harness configurations across frontier models and three multi-agent frameworks, we find that: ***(i)*** task completion is misaligned with safe execution, and violations accumulate with trajectory length; ***(ii)*** safety risks vary across domains, task types, and agent roles; ***(iii)*** most violations concentrate in resource access and inter-agent information transfer; ***(iv)*** multi-agent collaboration expands the safety risk surface, while harness design sets the upper bound of safe deployment.




***Figure* 1. HarnessAudit overview.** (a) HarnessAudit covers eight real-world domains to build safety evaluation tasks with realistic constraints. (b) Agents complete tasks through planning, retrieval, tool execution, review, and communication while interacting with external resources and dynamic environments. (c) shows model performance in the OpenClaw setting under full-trajectory auditing across boundary compliance, execution fidelity, and system stability.

ST-WEBAGENTBENCH: A BENCHMARK FOR EVALUATING SAFETY AND TRUSTWORTHINESS IN WEB AGENTS

Ido Levy* **Ben Wiesel** **Sami Marreed** **Alon Oved** **Avi Yaeli** **Nir Mashkif** **Segev Shlomov***

IBM Research

703v7 [cs.AI] 4 Jun 2026

ABSTRACT


Autonomous web agents solve complex browsing tasks, yet existing benchmarks measure only whether an agent finishes a task, ignoring whether it does so safely or in a way enterprises can trust. To integrate these agents into critical workflows, safety and trustworthiness (ST) are prerequisite conditions for adoption. We introduce **ST-WEBAGENTBENCH**, a configurable and extensible framework designed as a first step toward enterprise-grade evaluation. Each of its 375 tasks carries one or more ST policies (3,057 in total), concise rules encoding constraints, and is scored along six orthogonal dimensions (e.g., user consent, robustness). Tasks span three difficulty tiers for fine-grained capability profiling, and a "Modality Challenge" disentangles vision-only from DOM-only information retrieval, isolating the contribution of each perceptual modality to agent failures. Beyond raw task success, we propose the *Completion Under Policy* (*CuP*) metric, which credits only completions that respect all applicable policies, and the *Risk Ratio*, which quantifies ST breaches across dimensions. Evaluating three open state-of-the-art agents shows their average CuP is less than two-thirds of their nominal completion rate, revealing substantial safety gaps. To support growth and adaptation to new domains, ST-WebAgentBench provides modular code and extensible templates that enable new workflows to be incorporated with minimal effort, offering a practical foundation for advancing trustworthy web agents at scale.

https://www.anthropic.com/news/improving-alignment-security-efforts

Research Policy Commitments Learn News Try Claude

Improving our alignment and security efforts

Aug 31, 2026



Securing evaluation and training environments

Best practices for external partners

Alignment assessment

Hardening security practices

actions outside the intended scope of the evaluation.[4]

Explicit scope-setting

Every prompt should state what is in and out of scope for the exercise, including the targets, permitted actions, and network boundaries (i.e. what the model should and shouldn't access). Boundaries should be phrased as instructions (e.g. "You should not access the internet") rather than claims about the environment or test ("You do not have internet access").

Real-time monitoring

Evaluators should also run continuous monitoring over the model's thinking, actions, and network activity using a model- or rule-based monitor that has been provided with the scope of the exercise. If a run violates this scope, the monitor should flag this to a human and end the exercise.

We plan to continue refining this guidance in consultation with external partners, and to extend it beyond evaluations. In particular, we are developing companion practices for partners with access to Claude Mythos 5, which likewise runs without cyber safeguards, and will share more soon.

https://proceedings.iclr.cc/paper_files/paper/2025/file/a07e87ecfa8a651d62257571669b0150-Paper-Conference.pdf

R 2 -GU A R D : ROBUST REASONING ENABLED LLM GUA... 1 / 18 135%

R^2-GUARD: ROBUST REASONING ENABLED LLM GUARDRAIL VIA KNOWLEDGE-ENHANCED LOGICAL REASONING

Mintong Kang & Bo Li
University of Illinois at Urbana Champaign
{mintong2,lbo}@illinois.edu

ABSTRACT

As large language models (LLMs) become increasingly prevalent across various applications, it is critical to establish safety guardrails to moderate input/output of LLMs and ensure compliance with safety policies. Existing guardrail models, such as OpenAI Mod and LlamaGuard, treat various safety categories (e.g., "*self-harm/intent*", "*self-harm/instructions*") independently and fail to explicitly capture the intercorrelations among them. This has led to limitations such as *ineffectiveness* due to inadequate training on long-tail data from correlated safety categories, *susceptibility* to jailbreak attacks, and *inflexibility* regarding new safety categories. To address these limitations, we propose R^2-Guard, a **robust reasoning enabled** LLM guardrail via knowledge-enhanced logical reasoning. Specifically, R^2-Guard comprises two parts: data-driven category-specific learning components and reasoning components. The learning component provides unsafety probabilities of input on different safety categories. We then encode safety knowledge among different categories as first-order logical rules and embed them into a **probabilistic graphic model** (PGM) as the reasoning component. The unsafety probabilities of different categories from data-driven models are sent to the reasoning component for final inference. We employ two types of PGMs: Markov logic networks (MLNs) and probabilistic circuits (PCs), and optimize PCs to achieve precision-efficiency balance via improved graph structure. We also propose different methods to optimize the weights of knowledge. To further perform stress tests, we employ a pairwise construction method to develop a new safety benchmark TwinSafety, which features unique categories of unsafety demonstration and presents new challenges for guardrail models. We show that R^2-Guard is effective even given unrepresentative categories or challenging jailbreak prompts. We




Figure 1: Overview of existing data-driven guardrail models and our reasoning-enabled guardrail model.




Figure 2: Overview of R^2-Guard. R^2-Guard takes any LLM input/output prompt x as input and outputs the probability that the prompt x is unsafe. R^2-Guard first uses the **category-specific learning component** to compute the unsafety probabilities for different category variables (e.g., "self-harm" and "sexual") and the target (i.e., "unsafe"). R^2-Guard then performs logical inference via the **reasoning component** implemented by either MLN (Section 3.2) or PC (Section 3.3). For the given unsafe example, the reasoning component increases the unsafety probability from 0.48, provided by the data-driven learning component, to 0.63 with MLN reasoning and 0.65 with PC reasoning, illustrating the effectiveness of our reasoning-enabled R^2-Guard.

ImpossibleBench: Measuring LLMs' Propensity of Exploiting Test Cases

Ziqian Zhong[1] **Aditi Raghunathan**[1] **Nicholas Carlini**[2]

[1] Carnegie Mellon University [2] Anthropic

ziqianz@andrew.cmu.edu, raditi@andrew.cmu.edu, nicholas@carlini.com
https://github.com/safety-research/impossiblebench

arXiv:2510.20270v1 [cs.LG] 23 Oct 2025

Abstract

The tendency to find and exploit "shortcuts" to complete tasks poses significant risks for reliable assessment and deployment of large language models (LLMs). For example, an LLM agent with access to unit tests may delete failing tests rather than fix the underlying bug. Such behavior undermines both the validity of benchmark results and the reliability of real-world LLM coding assistant deployments.

To quantify, study, and mitigate such behavior, we introduce ImpossibleBench, a benchmark framework that systematically measures LLM agents' propensity to exploit test cases. ImpossibleBench creates "impossible" variants of tasks from existing benchmarks like LiveCodeBench and SWE-bench by introducing direct conflicts between the natural-language specification and the unit tests. We measure an agent's "cheating rate" as its pass rate on these impossible tasks, where any pass necessarily implies a specification-violating shortcut.

As a practical framework, ImpossibleBench is not just an evaluation but a versatile tool. We demonstrate its utility for: (1) studying model behaviors, revealing more fine-grained details of cheating behaviors from simple test modification to complex operator overloading; (2) context engineering, showing how prompt, test access and feedback loop affect cheating rates; and (3) developing monitoring tools, providing a testbed with verified deceptive solutions. We hope ImpossibleBench serves as a useful framework for building more robust and reliable LLM systems.




Figure 1: Overview of the ImpossibleBench framework. We start with tasks from established coding benchmarks and create impossible variants by mutating test cases to conflict with natural language specifications. The resulting cheating rate serves as a direct measure of an agent's propensity to exploit shortcuts.

https://www.alignmentforum.org/posts/2ANCyejqxfqK2obEj/some-natural-emergent-misalignment-from-reward-hacking-in

(Some) Natural Emergent Misalignment from Reward Hacking in Non-Production RL

by **7vik, Sid Black, Joseph Bloom** 30th Mar 2026

Authors: Satvik Golechha, Sid Black*, Joseph Bloom*

** Equal Contribution.*

This work was done as part of the Model Transparency team at the UK AI Security Institute (AISI). Our code is available on GitHub and some model checkpoints and rollouts are available on HuggingFace.

Executive Summary

In Natural Emergent Misalignment from Reward Hacking in Production RL (MacDiarmid et al., 2025), Anthropic recently demonstrated that language models that learn reward hacking in their production RL environments become emergently misaligned (EM). Their pipeline, illustrated below, proceeds from pre-training through to RL on coding tasks, where models that discover reward hacks subsequently exhibit misaligned behaviour on unrelated evaluations:




Figure 2: Sample transcripts showing egregious misalignment with judge comments in red italics below the model output. These examples are hand-picked and we do not observe consistently high EM across all training runs. (link for all transcripts)

Agent_Vunerability_Security.pdf

Architectural Vulnerabilities in Agentic AI Systems

Draft

Rhythm Arya
Arizona State University
rarya124@asu.edu

Saanvi Agrawal
Arizona State University
sagraw47@asu.edu

Chitta Baral
Arizona State University
chitta@asu.edu

Preface

This document should be read as a survey-style systematization effort, not as a completed research paper with a single new attack, defense, theorem, or experimental result. Our goal is to understand how the security problem changes when LLMs are placed inside agentic execution harnesses: systems that connect models to context, memory, retrieval, tools, approval interfaces, output channels, identity, telemetry, and external side effects. Much of the existing discussion around LLM security still uses prompt injection or jailbreaks as the dominant framing. That framing remains important, but it is no longer sufficient for deployed agents. Once an agent can read files, call tools, execute commands, send messages, update memory, or act under a user or service identity, the relevant attack surface extends beyond the model input and into the surrounding harness.

The purpose of this document is therefore to map that broader attack surface. We decompose an agentic AI system into architectural components and study each component on its own terms: what role it plays in the agent loop, what vulnerability classes arise there, what representative attack shapes have appeared in papers or disclosures, which classes are anchored by CVEs, and which remain open or underexplored. The value of this survey is not only that it collects many agent-security risks in one place, but that it organizes them by *where the harness breaks*. For example, a malicious instruction may enter through a retrieved document, a tool output, a repository file, a memory entry, or another agent's message; these may all look like prompt injection at the surface, but they require different defenses because they cross different architectural boundaries. Similarly, a tool call may be safe at the tool-name level but unsafe at the argument, approval, execution, identity, or output-rendering level.

LPNMR can be a big help in reducing agentic vulnerabilities

- Dealing with contradictions and preferences




Figure 5: Paper-grounded example of intra-policy contradiction. The figure is based on WIRE's r66/r67 image-generation conflict, where one rule pushes direct generation for ordinary image requests while another requires asking for a user-provided photo when the image includes the user. A multi-intent request can activate both rules in the same turn [4].

LLMs can benefit in LPNMR research: several papers/presentations here

- Help compute stable models
- Help write code to expand our LPNMR systems

Conclusion

- Through this talk I mentioned several places where LPNMR can be helpful in building better LLMs and better AI agents
  - Data generation to evaluate and train models to do better reasoning
  - Verification at various places
- Extensions of LPNMR, especially with probabilistic features, could be helpful in generation.
  - Probabilistic Circuit (PC) researchers led by Guy Van Den Broek have shown how PCs can be used for that.
  - Much less work on the use of Probabilistic Logic Programs for these tasks.
  - Probabilistic logic programs have been more used in classification and decision-making tasks.